

# Material Safety Data Sheet

## Touch 'n Seal U2-200 Foam Kit - PART A

Issue Date March 2009

Status Issued by AUS

### 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

<b>Product Name</b>	Touch 'n Seal U2-200FR Foam Kit - PART A	
<b>Product Use</b>	Part A Liquid Component of Polyurethane Spray Foam System	
<b>Company</b>	Australian Urethane Systems Pty Limited	
<b>Address</b>	25 Garling Road Kings Park NSW 2148	
<b>Emergency Tel.</b>	1800 039 008	<b>International:</b> + 800 2436 2255
<b>Telephone / Telex Number</b>	Tel: (02) 9678 9833	Fax: (02) 9678 9887
<b>Other Names</b>	<b>Name</b>	<b>Manf. Code</b>
	Polymethylene polyphenylene isocyanate, Polymeric MDI, Diphenylmethane-4,4- diisocyanate	U2-200FR-PART A

#### Other Information

### 2. HAZARDS IDENTIFICATION

Classified as hazardous according to criteria of NOHSC.

HAZARDOUS SUBSTANCE

DANGEROUS GOODS

<b>Risk Phrases:</b>	<b>R 20</b>	Harmful by inhalation.
	<b>R 36/37/38</b>	Irritating to eyes / irritating to respiratory system / irritating to skin.
	<b>R 42/43</b>	May cause sensitisation by inhalation / may cause sensitisation by skin contact.
<b>Safety Phrases:</b>	<b>S 26</b>	In case of contact with eyes, rinse immediately with plenty of water and contact medical advice or contact a Poisons Information Centre.
	<b>S 28</b>	After contact with skin, wash immediately with water and soap - warm, soapy water, if available.
	<b>S 38</b>	In case of insufficient ventilation, wear suitable respiratory equipment.
	<b>S 45</b>	In case of accident or if you feel unwell, contact a doctor or Poisons Information Centre immediately. (show the label if possible).

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients	Name	CAS	Proportion
	Polymethylene polyphenylisocyanate	9016-87-9	30 - < 60 % w/w
	Methylene bisphenyl isocyanate	101-68-8	30 - < 60 % w/w
	Methylenediphenyl diisocyanate	26447-40-5	< 10% w/w
	1,1,1,2 – Tetrafluoroethane	811-97-2	10 - < 30% w/w

---

#### 4. FIRST AID MEASURES

---

<b>Inhalation</b>	<p>Inhaling concentrated fluorocarbons from this product can cause unconsciousness, drowsiness, respiratory depression, rapid heartbeat and other symptoms. Persons with pre-existing heart disease may be at increased risk from exposure. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. May cause respiratory sensitisation in susceptible individuals. If any breathing difficulty occurs, keep patient calm, remove to fresh air, and if allergic reaction occurs seek medical attention.</p> <p>MDI concentrations below the exposure standards may cause allergic respiratory reactions in individuals already sensitised. Symptoms may include coughing, difficult breathing and a feeling of tightness in the chest. Effects may be delayed.</p>
<b>Ingestion</b>	<p>Immediately rinse mouth and drink plenty of water. Do not induce vomiting. Ingestion of this product causes vomiting, nausea and abdominal pain. Immediately refer to medical attention.</p>
<b>Skin</b>	<p>Avoid contact with skin. Wash immediately with plenty of warm water and soap. Remove any contaminated clothing. In case of contact with liquefied gas, thaw frosted parts with lukewarm water. If symptoms persist refer to medical attention. Prolonged or repeated exposure may cause skin irritation. May stain the skin. Skin contact may result in allergic skin reactions or respiratory sensitisation but is not expected to result in absorption of amounts sufficient to cause other adverse effects.</p>
<b>Eye</b>	<p>Irrigate with copious flowing water immediately and continuously for 15 minutes. May cause slight transient (temporary) eye irritation. Corneal injury is unlikely.</p>
<b>First Aid Facilities</b>	<p>Eye wash and normal washroom facilities.</p>
<b>Advice to Doctor</b>	<p>No specific antidote. Supportive care. Symptoms may appear later. Susceptible people may be sensitised to this product.</p>

---

#### 5. FIRE FIGHTING MEASURES

---

<b>Extinguishing Media</b>	<p>Foam, alcohol resistant foam, carbon dioxide and dry chemical. Keep containers cool with water spray</p>
<b>Hazards from Combustion Products</b>	<p>Produces oxides of carbon and nitrogen on combustion. May produce traces of hydrogen cyanide. May decompose in heat / fire releasing products of greater hazard.</p>
<b>Specific Precautions</b>	<p>Containers may explode when heated. Fire fighters to wear positive pressure self-contained breathing apparatus, safety glasses, boots, gloves and coveralls. Contain any run-off by diking to prevent entry into sewers, drains or water systems.</p>
<b>Specific Hazards</b>	<p>Isocyanate vapour and mist, carbon dioxide, carbon monoxide, nitrogen oxides and traces of hydrogen cyanide. Ruptured containers may rocket.</p>

---

#### 6. ACCIDENTAL RELEASE MEASURES

---

Evacuate and ventilate spill area. Contain spill by diking, to prevent entry into sewers, drains or water systems.

Wear full protective equipment including respiratory equipment during clean up. Avoid skin and eye contact. Wear gloves, safety glasses and coveralls. Avoid breathing vapours directly.

If possible position container so that the propellant gas escapes rather than the liquid.

For small spills of < 20 litres, absorb spilled material with inert absorbent (sand, vermiculite etc.) and put into open top containers - **do not make pressure tight**.

Do not permit to contaminate waterways, sewers or drains.

Transport to well-ventilated secure area (outside) and allow to stand for 48 hours.

Treat liquid with neutralising solution consisting of a mixture of 90% water, 5% detergent and 5% concentrated ammonium hydroxide [cloudy ammonia].

Add about 10 parts of the neutralising solution per part of liquid component with mixing. Allow to stand for 48 to 72 hours letting any evolved carbon dioxide escape. Do not seal. Residual contamination from spills can be cleaned up with the neutralising solution.

---

---

 7. HANDLING AND STORAGE
 

---

**Handling**

Wear the protective equipment as set out below when handling this product.

This product is under pressure in the container. Excessive exposure may cause irritation of the eyes, upper respiratory tract and lungs. Impaired lung function (decreased ventilatory capacity) has been associated with over-exposure to Isocyanates.

At room temperature, vapours are minimal due to low vapour pressure. Fresh air should be directed at personnel handling / using the product.

In any applications/operations where isocyanate aerosol or vapour concentrations are produced, exhaust ventilation must be provided to meet Exposure Standards. These include activities in which the material is heated, sprayed or otherwise mechanically dispersed such as drumming, venting or pumping.

Wear industrial safety clothing, as per details below:

Impervious plastic gloves - refer to  
AS 2161: Industrial Safety Gloves and Mittens

Safety goggles or Face Mask - refer to  
AS 1336: Recommended practices for eye protection in the industrial environment  
AS/NZS 1337: Eye protectors for industrial application

Respiratory Protection - refer to  
AS/NZS 1715: Selection, use and maintenance of respiratory protective devices

Clothing – refer to  
AS/NZS 2210: Occupational protective footwear. AS 2919: Industrial clothing

**Storage**

Keep containers closed at all times. Store indoors at 15 to 25°C in original, unopened containers.

Avoid product temperatures above 50°C and below 10°C. At temperatures below 10°C crystallisation may occur.

Store away from oxidising agents, acids, alkalis, direct sunlight or any source of ignition or heat.

---

 8. EXPOSURE CONTROLS / PERSONAL PROTECTION
 

---

**Exposure Limits**

Workplace Exposure Standard (ES) for Isocyanates, all (as –NCO): #

<b>TWA</b>	= 0.02 mg / m <sup>3</sup>	[ <b>TWA</b> = Time weighted average exposure]
<b>STEL</b>	= 0.07 mg / m <sup>3</sup>	[ <b>STEL</b> = Short term exposure limit]
<b>Sen.</b>		[ <b>Sen.</b> = Sensitiser]

# Exposure Standard for Atmospheric Contaminants in the Occupational Environment, published by Worksafe Australia.

[ For the 1,1,1,2 – Tetrafluoroethane [ Non-flammable HFC] – NHIS – July 2008  
**TWA Exposure Limit** = 1000 ppm / 4240 mg / m<sup>3</sup> ]

**Engineering Controls**

Use only in well ventilated area. Maintain air concentrations below Exposure Standards.

**Protective Equipment Personal**

Wear industrial safety clothing, as per details below. Always wash hands before smoking, eating, drinking or using toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Impervious PVC gloves - refer to AS 2161: Industrial Safety Gloves and Mittens

Safety goggles or Face Mask - refer to  
AS 1336: Recommended practices for eye protection in the industrial environment  
AS/NZS 1337: Eye protectors for industrial application

Respiratory Protection - refer to  
AS/NZS 1715: Selection, use and maintenance of respiratory protective devices

Clothing – refer to  
AS/NZS 2210: Occupational protective footwear. AS 2919: Industrial clothing

---

---

 9. PHYSICAL AND CHEMICAL PROPERTIES
 

---

<b>Appearance</b>	Clear amber liquid [Froths to an off white or yellowish color when released from container]
<b>Odour</b>	Mild musty odour
<b>pH</b>	Not applicable
<b>Vapour Pressure</b>	[For Polymeric Isocyanate < 0.01 Pascals (25°C)]
<b>Vapour Density</b> [Air = 1]	> 1
<b>Melting Point</b>	< 0°C
<b>Boiling Point</b>	For mixture: - 26°C @ 1 atm [for Polymeric Isocyanate component: > 208°C @ 1 atm]
<b>Solubility in Water</b>	Insoluble – reacts slowly with water
<b>Solubility in Organic Solvents</b>	Slightly soluble
<b>Specific Gravity</b> [Water = 1]	1.2 g/ml (25°C)
<b>Flashpoint</b>	Nil
<b>Ignition Temperature</b>	For mixture: Not tested [for Polymeric Isocyanate component > 600°C]
<b>Flammability</b>	Combustible. Vapour of product does not form flammable mixtures with the air at ambient temperatures.

---

 10. STABILITY AND REACTIVITY
 

---

<b>Stability</b>	Stable under normal conditions of storage. [Thermal decomposition > 230°C for Polymeric MDI]
<b>Hazardous Polymerisation</b>	Exothermic reaction with amines and alcohols. Reacts with water forming Carbon Dioxide gas, if In closed containers this may cause sufficient pressure build-up to burst containers.
<b>Materials to Avoid</b>	Water, acids, alkalis, alcohols, and metal compounds. Avoid water as it reacts to form heat and carbon dioxide. Enough heat and pressure can be produced to rupture a closed container. The reaction with water is slow at temperatures less than 49°C, but accelerated at higher temperature and in the presence of the above mentioned materials. Some reactions are violent.
<b>Hazards from Combustion Products</b>	Produces oxides of carbon and nitrogen on combustion. May produce traces of hydrogen cyanide. May decompose in heat/fire releasing products of greater hazard.

---

 11. TOXICOLOGICAL INFORMATION
 

---

<b>Inhalation</b>	<p>MDI concentrations below the exposure standards may cause allergic respiratory reactions in individuals already sensitised. Symptoms may include coughing, difficult breathing and a feeling of tightness in the chest. Effects may be delayed.</p> <p>Inhaling concentrated fluorocarbons from this product can cause unconsciousness, drowsiness, respiratory depression, rapid heartbeat and other symptoms. Persons with pre-existing heart disease may be at increased risk from exposure. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.</p> <p>LC<sub>50</sub> inhalation / rat / 4 hr exposure - 490 mg aerosol / m<sup>3</sup>. Concentration of the saturated vapour of Diphenylmethane-4,4-diisocyanate (MDIO @ 25°C – 0.09 mg/m<sup>3</sup>. 1,1,1,2- Tetrafluoroethane - LC<sub>50</sub> Inhalation / rat / 4 hr exposure – 1500 g/m<sup>3</sup>.</p>
<b>Ingestion</b>	<p>Ingestion of this product causes vomiting, nausea and abdominal pain. Single dose oral toxicity is considered to be extremely low.</p> <p>No hazards anticipated from swallowing small amounts incidental to normal handling operations.</p> <p>Polymeric MDI - LD<sub>50</sub> oral / rat - &gt; 10,000 mg/kg</p>
<b>Skin</b>	<p>Prolonged or repeated exposure may cause skin irritation. May stain the skin. Skin contact may result in allergic skin reactions or respiratory sensitisation but is not expected to result in absorption of amounts sufficient to cause other adverse effects.</p> <p>LD<sub>50</sub> dermal / rabbits &gt; 5,000 mg/kg.</p>
<b>Eye</b>	May cause slight transient (temporary) eye irritation. Corneal injury is unlikely.

<b>Chronic Effects</b>	<p>Systemic (Other Target Organ) Effects Tissue injury in the upper respiratory tract and lungs has been observed in laboratory animals after repeated excessive exposures to MDI / Polymeric MDI aerosols.</p> <p>Cancer Information Lung tumors have been observed in laboratory animals exposed to aerosol droplets of MDI / Polymeric MDI at 6mg/m<sup>3</sup> for their lifetime. Tumours occurred concurrently with respiratory irritation and lung injury. Only irritation was noted at the lower concentrations of 0.2 and 0.1 mg/m<sup>3</sup>. Current Exposure Standards are expected to protect against these effects.</p> <p>Teratology (Birth Defects) In laboratory animals, Polymeric MDI did not produce birth defects; other fetal effects occurred only at high doses, which were toxic to the mother.</p>
<b>Mutagenicity:</b>	Mutagenicity data on MDI are inconclusive. MDI was weakly positive in some in vitro (test tube) studies; other in-vitro studies were negative. A mutagenicity study in animals was negative.

---

## 12. ECOLOGICAL INFORMATION

---

	Do not allow to escape into waters, wastewater or soil.
<b>Movement &amp; Partitioning</b>	Movement in the environment is expected to be limited by the formation of insoluble polymers.
<b>Degradation &amp; Transportation</b>	Biodegradability: 0%, 28 days. Immiscible in water. Reaction with water at interface produces Carbon Dioxide and forms an insoluble and high melting point solid – polyurea. Degradation is expected in the atmospheric environment.
<b>Ecotoxicity</b>	Toxicity to fish: LC <sub>0</sub> (96 h) > 100 mg/l - Brachydanio rerio Aquatic invertebrates: EC <sub>50</sub> (24 h) > 750 mg/l – Daphnia pulex

---

## 13. DISPOSAL CONSIDERATIONS

---

<b>Liquid Residues</b>	<p>If after use a small amount of product remains, this can be disposed of by reaction with Mine Foam 200FR PART B Component [or a suitable Polyol blend – refer to Australian Urethane Systems Pty Ltd]. Mix one part of Mine Foam 200FR PART A with one part by volume of the Mine Foam 200FR PART B Component [or a suitable Polyol blend.] To decant liquid material remaining in tank, remove hose from valve outlet and fully open the valve to allow all pressure to dissipate. Unscrew valve mechanism and drain liquid residue. Mix in an open top container in well ventilated area, in &lt; 5 kg mix quantities. Wear full protective clothing as set out in Section 8. Allow 15 to 30 minutes cooling time between each mix to allow the reacted foam to cool before the next mix. After reaction into a solid foam product, dispose of in solid waste.</p> <p>For larger quantities refer to Australian Urethane Systems Pty Ltd.</p>
<b>Containers</b>	<p>To decant any remaining material remove hose from valve outlet and fully open the valve to allow all pressure to dissipate. Unscrew valve mechanism and drain liquid residue. Drain containers to remove ullage material. Rinse the container with a neutralising solution consisting of a mixture of 90% water, 5% industrial grade detergent and 5% concentrated ammonium hydroxide [cloudy ammonia] Allow neutralising solution to react for 48 hours in unsealed containers in external area. Absorb the rinse liquid into inert absorbent and hold in open containers to allow evaporation of water, then dispose of in solid waste. Dispose of cleaned container appropriately.</p>

---

---

 14. TRANSPORT INFORMATION
 

---

<b>UN Number</b>	UN1956
<b>Proper Shipping Name</b>	Compressed gas, n.o.s. (1,1,1,2- Tetrafluoroethane, Nitrogen)
<b>DG Class</b>	2.2
<b>Hazchem Code</b>	NA
<b>Packaging Group</b>	Not relevant
<b>EPG Number</b>	Nil
<b>IERG Number</b>	Nil

---

 15. REGULATORY INFORMATION
 

---

<b>Poisons Schedule</b>	Class 6	
<b>Hazard Category</b>	Symbol: Xn. Harmful. Irritant. Sensitiser.	
<b>Risk Phrases:</b>	<b>R 20</b>	Harmful by inhalation.
	<b>R 36/37/38</b>	Irritating to eyes / irritating to respiratory system / irritating to skin.
	<b>R 42/43</b>	May cause sensitisation by inhalation / may cause sensitisation by skin contact.
<b>Safety Phrases:</b>	<b>S 26</b>	In case of contact with eyes, rinse immediately with plenty of water and contact medical advice or contact a Poisons Information Centre.
	<b>S 28</b>	After contact with skin, wash immediately with water and soap - warm, soapy water, if available.
	<b>S 38</b>	In case of insufficient ventilation, wear suitable respiratory equipment.
	<b>S 45</b>	In case of accident or if you feel unwell, contact a doctor or Poisons Information Centre immediately. (show the label if possible).
<b>Other CAS Numbers / Products</b>	Diphenylmethane – 4,4' – di-isocyanate	101-68-8
	Methylenediphenyl diisocyanate	26447-40-5

---

 16. OTHER INFORMATION
 

---

<b>Issue Date</b>	March 2009
<b>References</b>	<p>Worksafe Australia Guide - "ISOCYANATES" - July 1990.          National Occupational Health and Safety Commission.          Australian Government Publishing Service Canberra.          Code WAP 90/017 GS O12-1990.</p> <p>Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment  <i>Hazardous Substances Information System – 30 July 2008</i>          Department of Education, Employment and Work Place Relations, Office of the Australian Safety and Compensation Council.</p>

**Copyright: Australian Urethane Systems Pty Ltd**

Information provided has been prepared in good faith and believed to be correct. Australian Urethane Systems make no warranty either express or implied as to completeness, accuracy thereof, misuse or misinterpretation of this information.

---

**END OF MSDS**


---